

Acrylic Texture

1 component acrylic texture coating



| Introduction

Alka Acrylic Texture Coating is a decorative and protective wall or ceiling finish made from **acrylic-based resins** combined with aggregates such as sand or fine particles to create a textured surface. It is applied to both interior and exterior surfaces to enhance appearance, hide minor imperfections, and provide long-lasting protection.

Key Features

- **Decorative finish** – Creates various textures and patterns, from subtle to heavily textured effects.
- **Durability** – Resists cracking, peeling, and weathering better than many traditional coatings.
- **Flexibility** – Acrylic resins allow the coating to expand and contract with building movement, reducing cracks.
- **Water resistance** – Helps protect surfaces from moisture penetration while remaining breathable.
- **UV resistance** – Maintains color and appearance when exposed to sunlight.
- **Low maintenance** – Easy to clean and generally requires less frequent repainting.

| Where it could be used.

- Exterior walls and facades
- Interior feature walls
- Concrete, masonry, brick, and rendered surfaces
- Commercial, residential, and industrial buildings

| Benefits

Acrylic texture coatings improve aesthetics, conceal surface defects, increase weather protection, and can extend the lifespan of building surfaces. They are commonly used where both decorative appeal and surface durability are desired.

| How to Apply

Surface Preparation

Use our Primer if you are painting over bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber.

Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution.

Fill cracks and imperfections with a suitable filler and spot prime.

All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.

Application

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper.

Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

Thinning

Depending on the situation, you can mix 5% to max of 10% water for easier application.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

| Important Notes

- Do not add any solvents.
- Always ensure good ventilation when using Alka Ceiling Paint in a confined space.
- Freshly applied Alka Ceiling Paint should be protected from damp, condensation and water for at least 24 hours.
- If in doubt about the use or application of this product, or further information please contact our Alka Technical Department.
- Avoid contact with skin and eyes.
- Wear protective gloves and eye protection during work.
- If skin contact occurs, wash skin thoroughly.
- If in eyes, hold eyes open, flood with warm water and seek medical attention without delay.
- Avoid contact with foodstuffs and utensils.

Acrylic Texture

1 component acrylic texture coating



A full Material Safety Data Sheet is available from Alka on request.

Technical and Physical Data

Colour	White, Pastels & Mid-tone Colours
Gloss	0-3%
Coverage	Up to 2 m ² /L per coat. Practical coverage may depend on surface profile, method of application and losses.
VOC	<1 g/L
Volume Solids	30-45%
Dry times	Touch Dry: 30 minutes @ 20°C approx. Recoat: 4-6 hours @ 20°C approx.
Storage	Minimum of 12 months in unopened containers when stored free from frost in dry conditions between 10°C and 50°C. Component B is classed as non-hazardous for transportation.
Packaging	15L

All products are subject to Alka terms and conditions. Read the full version on our website prior to any purchase.

| Contact us

ALKA COATINGS / ABN: 70 652 323 487

24/7 Toll-Free Emergency Response line for SDS: 1800 921 288

87 Market St, Smithfield 2164, New South Wales, Australia.

Phone: 1300 51 51 50 / www.alka.au

info@alka.au / Find us on social media.