

| Introduction

Alka Exterior Paint is a premium quality self-priming 100% acrylic water based semi-gloss finish for exterior use on concrete, cement, bare timber, brick, fibre-cement board, masonry and galvanized iron. The product is easy to apply, has excellent coverage and low dirt pickup. Self-priming in most cases and quick drying. Water wash up for your paint equipment and no harsh solvent odour.

Alka Exterior paint is a protective and decorative coating designed for outdoor surfaces such as walls, facades, fences, and building exteriors. It is formulated to withstand harsh weather conditions, including sunlight, rain, wind, humidity, and temperature changes. Exterior paints provide strong adhesion, durability, colour retention, and resistance to cracking, peeling, fading, and mold growth. They help protect building materials from moisture penetration and environmental damage, extending the life of the surface. Available in various finishes and colours, exterior paint enhances a building's appearance while delivering long-term protection. Common substrates include concrete, brick, render, timber, metal, and masonry.

| Where it could be used.

Timber, weatherboards, concrete, plaster, concrete blocks, brickwork, cement render, wallboard PVC and cement sheets. Though designed primarily for exterior use, it may also be used inside in areas prone to high wear. For Exterior & Interior use.

| Benefits

- **Weather Protection** – Shields surfaces from rain, UV radiation, wind, and temperature fluctuations.
- **Prevents Moisture Damage** – Helps reduce water penetration, which can cause cracking, peeling, mold, and structural deterioration.
- **Improves Durability** – Protects building materials from environmental wear, extending their service life.
- **Resists Fading** – Maintains colour and appearance despite prolonged exposure to sunlight.
- **Enhances Appearance** – Refreshes and improves the look of a building with a wide range of colours and finishes.
- **Reduces Maintenance Costs** – Durable coatings require less frequent repainting and repairs.
- **Protects Against Biological Growth** – Many formulations resist mold, mildew, algae, and fungal growth.
- **Improves Surface Performance** – Helps prevent cracking, chalking, and peeling caused by outdoor exposure.
- **Increases Property Value** – A well-maintained exterior can improve curb appeal and perceived property value.
- **Suitable for Various Substrates** – Can be applied to concrete, brick, render, timber, metal, and other exterior surfaces when properly prepared.

| How to Apply

Surface Preparation

Use our Primer if you are painting over bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber.

Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution.

Fill cracks and imperfections with a suitable filler and spot prime.

All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.

Application

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper.

Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

Thinning

Not recommended unless spraying; Up to 10% of water may be added.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

| Important Notes

- Do not add any solvents.
- Always ensure good ventilation when using Alka Ceiling Paint in a confined space.
- Freshly applied Alka Ceiling Paint should be protected from damp, condensation and water for at least 24 hours.
- If in doubt about the use or application of this product, or further information please contact our Alka Technical Department.
- Avoid contact with skin and eyes.
- Wear protective gloves and eye protection during work.
- If skin contact occurs, wash skin thoroughly.
- If in eyes, hold eyes open, flood with warm water and seek medical attention without delay.
- Avoid contact with foodstuffs and utensils.

Alka Exterior Paint

1 component water-based acrylic exterior semi-gloss paint



A full Material Safety Data Sheet is available from Alka on request.

Technical and Physical Data

Colour	White & Tint bases. Standard colours available upon request.	
Gloss Level @ 60° head	25% - 35%	
Coverage	Up to 10-14 m ² /L. Practical coverage may depend on surface profile, method of application and losses.	
VOC	<1 g/L	
Volume Solids	35%	
Dry times	Touch Dry:	30 minutes @ 20°C approx.
	Recoat:	2 hours @ 20°C approx.
Film Build at 16 m²/L	Dry 17 µm Wet 63 µm	
Storage	Minimum of 12 months in unopened containers when stored free from frost in dry conditions between 10°C and 50°C. Component B is classed as non- hazardous for transportation.	
Packaging	4L, 10L, 15L & 20L.	

All products are subject to Alka terms and conditions. Read the full version on our website prior to any purchase.

| Contact us

ALKA COATINGS / ABN: 70 652 323 487

24/7 Toll-Free Emergency Response line for SDS: 1800 921 288

87 Market St, Smithfield 2164, New South Wales, Australia.

Phone: 1300 51 51 50 / www.alka.au

info@alka.au / Find us on social media.