

| Introduction

Alka Primer Paint is a premium quality, fast drying, water based, interior and exterior, multipurpose primer/sealer/undercoat.

Alka Primer Paint is formulated primarily to provide a sealed and sand able surface for acrylic and solvent based topcoats. Combines the qualities desired in an interior/exterior primer: Excellent adhesion, and filling properties, low spatter, sand-ability, minimal odour, excellent flow and levelling.

May be applied by brush, roller or spray. Contain anti fungicidal additives and may be tinted to facilitate contrasting colours. It is environmentally friendly, non-toxic, nonhazardous and non-flammable.

| Where it could be used.

Alka Primer Paint is recommended for:

Wallboard, Plasterboard, interior timber and exterior plaster and concrete. This product is suitable for application on previously painted or unpainted surfaces. If using over plastered surfaces, use this product only after complete curing and cleaning of plaster. It is also for interior and exterior use.

| Benefits

- **Excellent Durability** – Forms a hard-wearing coating that resists everyday wear, making it suitable for high-traffic and high-touch areas.
- **Non-Yellowing** – Maintains its original colour and gloss over time, unlike many traditional oil-based gloss paints.
- **Water-Based Formula** – Lower odour, easier cleanup with water, and generally more user-friendly than solvent-based enamels.
- **Fast Drying** – Dries quickly, allowing faster recoating and project completion.
- **Good Washability** – The glossy surface is easier to clean and maintain, making it ideal for kitchens, bathrooms, and laundries.
- **Interior and Exterior Use** – Suitable for a wide range of applications both inside and outside buildings.
- **Good Flow and Finish** – Designed to level out smoothly, helping achieve a professional-looking result with minimal brush marks.
- **UV and Weather Resistance** – Helps retain appearance and performance when exposed to sunlight and outdoor conditions.
- **Low Maintenance** – Its durable, washable finish reduces the need for frequent repainting and touch-ups.

| How to Apply

Surface Preparation

Remove all dirt, dust and grease from the bare surface. If some mould or fungus is present on the surface, wash it with a commercially available bleaching agent and then treat with antifungal solution.

Fill cracks and imperfections with a suitable filler and spot prime.

All previously painted surfaces should be sanded to remove loose/flaking paint and to reduce previous film to a flat finish.

Application

Brush, Roller or Spray. Stir the contents thoroughly before and during use. Apply one or two uniform coats with light sanding in between using 220-grit sandpaper.

Brush, Roller or Spray. Please use the method best suited to your requirement and skill. The use of a synthetic sleeve of 10 mm pile on a smooth surface is recommended. For airless spray application, optimum pressure of 2700 psi and nozzle size of 0.013-0.015 is suggested as a guideline.

Dust off and follow with two finish coats. Care must be taken to maintain wet edge when rolling large surfaces. When applying by spray application, back roll when wet to eliminate plaster set joint smooth setting. Do not over roll as glancing light may affect the finished surface.

Thinning

Not recommended unless spraying; Up to 10% of water may be added.

Protect our environment

- Do not wash painting equipment and allow waste to enter drains and water ways.
- Do not dispose of unwanted paint and thinners that will enter drains and water ways.

| Important Notes

- Do not add any solvents.
- Always ensure good ventilation when using Alka Trim Paint in a confined space.
- Freshly applied Alka Trim Paint should be protected from damp, condensation and water for at least 24 hours.
- If in doubt about the use or application of this product, or further information please contact our Alka Technical Department.
- Avoid contact with skin and eyes.
- Wear protective gloves and eye protection during work.
- If skin contact occurs, wash skin thoroughly.
- If in eyes, hold eyes open, flood with warm water and seek medical attention without delay.
- Avoid contact with foodstuffs and utensils.

Alka Primer Paint

water-based acrylic 3-in-1 primer/sealer/undercoat paint



A full Material Safety Data Sheet is available from Alka on request.

Technical and Physical Data

Colour	White. (Sheen: Flat)
Coverage	Up to 14 m ² /L. Practical coverage may depend on surface profile, method of application and losses.
VOC	<1 g/L
Dry times	Touch Dry: 30 minutes @ 20°C approx. Recoat: 2 hours @ 25°C approx. or 3 hours @ 20°C approx.
Film Build at 16 m²/L	Dry 17 µm Wet 63 µm
Storage	Minimum of 12 months in unopened containers when stored free from frost in dry conditions between 10°C and 50°C. Component B is classed as non- hazardous for transportation.
Packaging	4L, 10L, 15L, 20L.

All products are subject to Alka terms and conditions. Read the full version on our website prior to any purchase.

| Contact us

ALKA COATINGS / ABN: 70 652 323 487

24/7 Toll-Free Emergency Response line for SDS: 1800 921 288

87 Market St, Smithfield 2164, New South Wales, Australia.

Phone: 1300 51 51 50 / www.alka.au

info@alka.au / Find us on social media.